

5

10

**APPLICATION**  
**FOR**  
**UNITED STATES LETTERS PATENT**  
**ON**  
**APPARATUS AND METHOD OF FILLING A MOLD FOR**  
**MANUFACTURING AN OPHTHALMIC LENS**

15

**BY**

20

**Kai C. Su, a citizen of the United States, residing at 10390 Hopewell Road,  
Alpharetta, Georgia 30201.**

## **APPARATUS AND METHOD OF FILLING A MOLD FOR MANUFACTURING AN OPHTHALMIC LENS**

This application is a continuation-in-part of U.S. Application Serial No.  
5 09/343,802 filed on June 30, 1999, which status now was abandoned and itself was a  
continuation-in-part of U.S. Application Serial No. 09/026,222 filed on February 19,  
1998, entitled "Method for Curing a Lens-Forming Liquid," which was issued on  
August 15, 2000 as U.S. Patent No. 6,103,148. Both U.S. Application Serial No.  
09/343,802 and U.S. Application Serial No. 09/026,222 are hereby incorporated herein  
10 in their entireties by reference.

### **BACKGROUND OF THE INVENTION**

#### **Field of the Invention**

15 The present invention relates to an apparatus and method of filling a mold for  
manufacturing an ophthalmic lens.

#### **Background Art**

Most lenses today are made by molding plastic because of its light weight,  
20 density, refractive index, and impact resistance. To form a lens, two molding shells,  
often referred as a front mold and a back mold in the art of lens making, are used. Each  
molding shell has a facing inside surface. When these two molding shells are properly  
positioned at a desired distance and rotational orientation to each other, their facing  
inside surfaces are a negative image of the surfaces of the lens to be formed. A closure  
25 member is used to cooperate with the molding shells to form a mold with a molding  
cavity. Then a fluid lens-forming material, normally a liquid monomer, is inserted into  
and contained in the molding cavity defined by the two molding shells and the closure  
member. The closure member normally has a casting opening through which the fluid  
lens-forming material is introduced into the cavity. Once the fluid lens-forming  
30 material is in the cavity, it is cured to form a hardened polymeric lens taking the shape  
of the molds.

Currently, there are two ways to fill a mold in molding the lenses in the art. The first, conventional way is a "top" filling method as shown in Fig. 1 of this specification. In Fig. 1, a mold M with a molding cavity C is vertically positioned so that an opening V is at the top of the mold M. A filling device (not shown) in connection with a  
5 reservoir of a fluid lens-forming material delivers the fluid lens-forming material into the molding cavity C through a filling needle via the opening V. The opening V also functions as an air venting channel during the process. Inevitably, some air bubbles B generated during the filling process may be easily trapped at the opening V and may form an air block that slows down the filling process. Moreover, the "syrup" effect well  
10 known to glass makers is also evident with this "top" filling method. That is, given the viscosity of the lens-forming material, the fluid flows slowly, in "runs," into the molding cavity C and the air block formed at the opening V further frustrates the filling process. Because of the uneven, slow flow of the fluid lens-forming material into the molding cavity C, the likelihood of optical defects in the resulting lens is increased.

15 The second filling method is a "bottom" filling method as shown in Fig. 2 of this specification. In Fig. 2, a casting opening O is separated from the venting opening V in about 180°. The mold M is positioned so that the casting opening O is located at the bottom of the mold M. The lens-forming material is introduced into the molding  
20 cavity C from the bottom through the casting opening O. To overcome gravity, pumping means (not shown) may be used to cause the lens-forming material to flow into the cavity C without significantly pressurizing it. Air venting is provided through the venting opening V located at the top of the molding cavity C. Because this filling method separates the venting opening from the casting opening, the interference of air  
25 bubbles with the flow of the fluid lens-forming material is eliminated and the "syrup" effect is reduced greatly. Thus, it is able to shorten the filling process significantly.

However, the bottom filling method introduces a potential new quality problem. As known to the people skilled in the art, the center region of a formed optical lens is  
30 the most optically active area. Therefore, any defect in this region will compromise the quality of the formed lens. Because air bubbles inevitably produce optical defects, it is preferred not to allow the air bubbles to pass through this optically active region.

However, as shown in Fig. 2, the air bubbles B have to travel through the most optically active region to reach the venting opening V. In fact, the air bubbles B cross the entire molding cavity C, which significantly increases the likelihood of optical defects in the finished lens. Thus, the bottom filling method may seriously compromise  
5 the optical quality of the formed optical lens.

Accordingly, there exists a need for an improved apparatus and method for filling a mold for molding optical lenses.

10

## SUMMARY OF THE INVENTION

The present invention overcomes the disadvantages of the prior art and discloses an entirely new method of filling a mold for molding lens and related apparatus. In one aspect, the present invention relates to a method for molding an  
15 optical lens. In one embodiment, the method includes the steps of providing a mold having two molding shells disposed on edge and substantially vertically oriented, and an annular closure member having an outer surface disposed at the periphery of the molding shells cooperating with the two molding shells to define a molding cavity having a center, a vertical axis and a horizontal axis perpendicular thereto, both axes  
20 passing through the center to thereby divide the mold into an upper portion and a lower portion, a venting opening and a casting port disposed at the upper portion of the mold and spaced apart from each other at an acute angle, wherein the venting opening is in fluid communication with the ambient air and the molding cavity, and the casting port is separated from the ambient air by the outer surface of the closure member and in  
25 fluid communication with the molding cavity, introducing a fluid lens-forming material into the molding cavity through the casting port, curing the fluid lens-forming material so that the fluid lens-forming material is hardened to form the optical lens, and removing the optical lens from the molding cavity.

30

Because of the separation and the special geometric arrangement of the venting opening and the casting port, the fluid lens-forming material is filled into the molding cavity without interference from the air venting process. Any trapped air bubbles travel

to the venting opening and out of the mold from there due to gravity without passing through the optically active area of the optical lens formed. Moreover, the filling of the fluid lens-forming material is further facilitated by gravity and a pumping device is no longer necessary. Thus, the present invention avoids the "syrup" effect, improves the  
5 quality of the lens formed and further facilitates the filling process.

In another aspect, the present invention relates to a method for molding an optical lens. In one embodiment, the method includes the steps of providing a mold having two molding shells disposed on edge and substantially vertically oriented, and  
10 an annular closure member disposed at the periphery cooperating with the two molding shells to define a molding cavity which has a center, a vertical axis and a horizontal axis perpendicular to each other, both axes passing through the center to thereby divide the mold into an upper portion and a lower portion, a venting opening disposed at the upper portion of the mold and communicating with the molding cavity, injecting a fluid  
15 lens-forming material into the molding cavity through a port at a position at the upper portion of the mold but apart from the location of the venting opening at acute angle, wherein the port is separated from the ambient air by the outer surface of the closure member, curing the fluid lens-forming material so that the fluid lens-forming material is hardened to form the optical lens, and removing the optical lens from the molding  
20 cavity.

In a further aspect, the present invention relates to a method for molding an optical lens. In one embodiment, the method includes the steps of providing a mold having two molding shells disposed on edge and substantially vertically oriented, and  
25 an annular closure member having an outer surface disposed at the periphery cooperating with the two molding shells defining a molding cavity with a center and having a vertical axis and a horizontal axis perpendicular to each other, both axes passing through the center thereby dividing the mold into an upper portion and a lower portion, a venting opening and a plurality of casting openings disposed at the upper  
30 portion of the mold and spaced apart from each other, the venting opening and each of the casting openings forming an acute angle between them, the venting opening and the plurality of casting openings communicating with the molding cavity, wherein at least

one of the plurality of casting openings is a port being separated from the ambient air by the outer surface of the closure member, introducing a fluid lens-forming material into the molding cavity through a casting opening, curing the fluid lens-forming material so that the fluid lens-forming material is hardened to form the optical lens, and  
5 removing the optical lens from the molding cavity.

In yet another aspect, the present invention relates to an apparatus for molding an optical lens. In one embodiment, the apparatus includes a front mold, a back mold, and a closure member having an outer surface and cooperating with the front mold and  
10 the back mold to form a molding cavity therebetween for molding the optical lens. The closure member has at least one venting opening and at least one casting port spaced apart from each other at an acute angle at an upper portion of the molding cavity, the venting opening being in fluid communication with the molding cavity and the ambient air and the casting port being in fluid communication with the molding cavity and  
15 separated from the ambient air by the outer surface of the closure member.

In yet a further aspect, the present invention relates to an improvement in an apparatus for molding an optical lens. The apparatus includes a pair of opposed molding shells disposed on edge and substantially vertically oriented and which form a  
20 molding cavity therebetween with a closure member having an outer surface, the molding cavity having a center, a vertical axis and a horizontal axis perpendicular to each other, a casting port being separated from the ambient air and communicating with the cavity for the introduction therethrough into the cavity a fluid lens-forming material and a venting opening communicating into the cavity. In one embodiment, the  
25 improvement includes the venting opening being disposed at the upper most point of the molding cavity, where the vertical axis intersects the closure member, the venting opening and the casting port forming an acute angle therebetween at an upper portion of the molding cavity.

30 In another aspect, the present invention relates to an apparatus for molding an optical lens. In one embodiment, the apparatus includes a front mold, a back mold, and a closure member having an inner surface and an outer surface and cooperating with the

front mold and the back mold to form a molding cavity therebetween for molding the optical lens. The closure member has at least one venting opening and at least one casting port spaced apart from each other at an acute angle at an upper portion of the molding cavity, the venting opening and the casting port being connected by a recess  
5 channel located at the inner surface.

In all of the embodiments above, the closure member can be in the form of a gasket or a sleeve. For the latter, the sleeve can be formed from an elastomeric material. Thus, a filling needle can be used to pierce the elastomeric sleeve and then  
10 inject the fluid lens-forming mixture into the molding cavity.

The venting opening and casting opening can be pre-manufactured, or they may be formed during the filling process by, say, a filling needle. The sizes of the venting opening and the casting opening may be same or may be different.  
15

In a further aspect, the present invention relates to a strip for molding an optical lens in cooperation with a front mold and a back mold. In one embodiment, the strip includes a body having a first end, a second end, and an inner surface and an opposed outer surface, and a recess channel formed on the inner surface. The recess channel can  
20 be formed on the inner surface continuously, extending from the first end to the second end of the body. Alternatively, the recess channel can be formed on the inner surface discontinuously. In use, the strip can be wrapped around the edges of the front mold and the back mold to form a sleeve cooperating with the front mold and the back mold to define a molding cavity.  
25

In yet another aspect, the present invention relates to a sleeve for molding an optical lens in cooperation with a front mold and a back mold. In one embodiment, the sleeve includes a body portion having a first end and a second end, an inner surface and an opposed outer surface, a bore extending from the first end and the second end  
30 axially, a venting port formed on the body portion, a casting port formed on the body portion and positioned apart from the venting port, and a recess channel formed on the inner surface connecting the venting port and the casting port. The recess channel can

be formed to extend continuously from the venting port and the casting port. The bore is adapted to receive the front mold and the back mold to define a molding cavity. Additionally, the casting port is formed intermediate the outer surface of the body portion and the bore such that the casting port is separated from the ambient air by the  
5 outer surface of the body portion and is in fluid communication with the molding cavity.

These and other aspects will become apparent from the following description of various embodiments taken in conjunction with the following drawings, although  
10 variations and modifications therein may be affected without departing from the spirit and scope of the novel concepts of the disclosure.

#### **BRIEF DESCRIPTION OF THE FIGURES OF THE DRAWINGS**

15 Fig. 1 is a vertical cross-sectional view of a prior art filling a mold from the top of the mold.

Fig. 2 is a vertical cross-sectional view of a prior art filling a mold from the bottom of the mold.

20 Fig. 3 is a perspective view of a mold according to one embodiment of the present invention with a portion of the closure member broken away for clarity.

Fig. 4 is a vertical cross-sectional view of the closure member of Fig. 3.

25 Fig. 5 is a vertical cross-sectional view of a second embodiment of the closure member used in the present invention.

30 Fig. 6 is a vertical cross-sectional view of a third alternative embodiment of the closure member used in the present invention.



Fig. 7 is a vertical cross-sectional view of a fourth embodiment of the closure member used in the present invention.

Fig. 8 is a perspective view of a strip used in the present invention.

5

Fig. 9 is a perspective view of an alternative embodiment of the strip used in the present invention.

Fig. 10 is a perspective view of an embodiment of the closure member in the form of a sleeve, partially in schematic, of the present invention by utilizing the strip as shown in Fig. 9.

10

Fig. 11 is a perspective view of another alternative embodiment of the strip used in the present invention.

15

Fig. 12 is a perspective view of an embodiment of the closure member in the form of a sleeve, partially in schematic, of the present invention by utilizing the strip as shown in Fig. 11.

20

Fig. 13 is a cross-sectional view of the closure member in the form of a gasket, partially in schematic, of the present invention.

## DETAILED DESCRIPTION OF THE INVENTION

25

The present invention is more particularly described in the following examples that are intended as illustrative only since numerous modifications and variations therein will be apparent to those skilled in the art. As used in the specification and in the claims, "a" can mean one or more, depending upon the context in which it is used.

30 The embodiments are now described with reference to the figures, in which like numbers indicate like parts throughout the figures.

Referring generally to Figs. 3-7, the present invention relates to an apparatus and method of filling a mold 10 for manufacturing an optical lens. The mold 10 is formed by two molding shells 12A, 12B disposed on edge and an annular closure member 14 at the periphery of the molding shells 12A, 12B, defining between them a  
5 molding cavity 16.

In one embodiment, the molding shells 12A, 12B are rotationally aligned relative to each other and axially positioned apart from each other at the desired axial separation distance (e.g., the appropriate separation to produce a lens of a desired  
10 thickness). When properly positioned, the facing inside surfaces of the molding shells 12A, 12B are a negative image of the required opposing surfaces of the optical lens to be formed. These surfaces are coaxial in the embodiments shown with a common axis A. Cross-sectionally, they have a common center 13. Thus, if the molding shells 12A, 12B are disposed on edge, the axis A is substantially horizontal and the molding shells  
15 11A, 11B are substantially vertical. Moreover, as shown in Figs. 4-7, the molding cavity 16, and thus the mold 10, can be divided into an upper portion 11A and a lower portion 11B by a horizontal axis X which passes through the center 13. The mold 10 has a vertical axis Y (not shown), which is perpendicular to the axis X and passes through the center 13.

20

As shown in Figs. 3-7, the molding shells 12A, 12B have a generally circular outside contour. Alternatively, the contour may take other suitable geometric shapes such as oval, rectangular, or square. The intersection of the axis Y and the outside contour of the upper portion of 11A defines a highest or upper most point 17 of the  
25 molding cavity 16.

The closure member 14 in the embodiment shown in Fig. 3 is in the form of a tubular sleeve. The tubular sleeve engages the edges of the molding shells 12A, 12B to form the molding cavity 16. The sleeve can be formed from a strip which is wound  
30 around the edges of the molding shells 12A, 12B. This strip may be an adhesive synthetic material or a heat-shrink material so that the formed sleeve adheres to the molding shells. Alternatively, the strip can be an elastomeric and nonadhesive material

so that the resulting sleeve allows the molding shells 12A, 12B to slide along the axis A during the curing process to compensate for the shrinkage of the lens-forming material. Additionally, the closure member 14 may be in the form of a gasket.

5           The closure member 14 has a venting opening 18 and a casting opening 20. The venting opening 18 is in communication with the molding cavity 16 so that the air may be vented out from the molding cavity 16. In the embodiments shown, the venting opening 18 is in the upper portion 11A of the molding cavity 16, substantially at or adjacent the upper most point 17 of the molding cavity 16.

10

          The casting opening 20 is also in communication with the molding cavity 16 so that a fluid lens-forming material may be introduced through it into the molding cavity 16. The casting opening 20 is also located in the upper 11A portion of the molding cavity 16 as well, but apart from the venting opening 18. In accordance with the  
15       present invention, as shown in Figs. 3-7, the position of the venting opening 18 is always higher than the position of the casting opening 20 so that air bubbles can readily be vented outward there through. Moreover, as shown in Fig. 4, the venting opening 18 and the casting opening 20 form an angle,  $\alpha$ , therebetween. The angle  $\alpha$  can be viewed as the angle between the axis  $L_1$ , which is a radial axis connecting the center 13 and the  
20       center of the casting opening 20, and the axis  $L_o$ , which is a radial axis connecting the center 13 and the center of the venting opening 18. For the embodiments shown in Figs. 3-7, the axis  $L_o$  merges with the axis Y, although it does not have to.

          The present invention requires that the angle  $\alpha$  be an acute angle. This ensures  
25       that during the filling process, the air bubbles B will not travel through the most optically active area of the lens to reach the venting opening 18. Instead, the bubbles likely will travel along the inside surface of the closure member 14 to reach the venting opening 18 as shown in Fig. 4. Indeed, because of gravity, the air bubbles B will always be above the surface of the lens-forming fluid filled in the molding cavity  
30       during the filling process. Thus, the present invention makes it possible that the most optically active area of the lens may not be disturbed at all.

In the present invention, while the angle  $\alpha$  may take any nonzero value between 0 to 90°, the preferred range for the angle  $\alpha$  is 5° to 85°, and the optimal range for the angle  $\alpha$  is 5° to 50°. It is understood that although the casting opening 20 shown in Figs. 3 and 4 is on the right of the venting opening 18, the casting opening 20 may be located at the left as well as shown in Fig. 5.

The casting opening 20 may be a hole as shown in Figs. 3-5. Cross-sectionally, the casting opening 20 may be in circular, oval, or other proper geometric shapes. Similarly, the venting opening 18 may be a hole in practice as shown in Figs. 3-5. Cross-sectionally, the venting opening 18 may be in circular, oval, or other proper geometric shapes. The venting opening 18 and the casting opening 20 may be identical, or different, size-wise and shape-wise.

Alternatively, as shown in Fig. 7, the venting opening 18 may be in association with a venting port 22. Similarly, the casting opening 20 may be associated with a casting port 24. The venting port 22 may be used to support a conventional air pump (not shown) for creating a suction to facilitate air venting. The casting port 24 may be used to support or position a filling needle (not shown) for better filling. Additional embodiments of the casting port are discussed below.

In the embodiments shown in Figs. 3-7, the venting opening 18 and the casting opening 20 can be pre-manufactured. Alternatively, for the embodiment where the closure member 14 is formed of elastomeric material or other synthetic material, the venting opening 18 and the casting opening 20 may be formed by a filling needle directly piercing through the closure member 14 before or during the filling process.

The fluid lens-forming material is introduced into the molding cavity 16 through the casting opening 20. The filling can be done at a filling station (not shown) where the mold 10 is disposed substantially vertically so that the venting opening 18 is located at or adjacent the upper most point 17 of the molding cavity 16. During the filling process, a filling needle (not shown) is used for injecting a desired amount of the fluid lens-forming material into the molding cavity 16. The filling needle is connected

to a reservoir (not shown) of the fluid lens-forming material. The filling needle enters the casting opening 20, if one has been pre-manufactured, or pierces the closure member 14 to create one if not. Either way, the filling needle establishes fluid communication between the reservoir and the molding cavity 16 through the casting opening 20. The filling needle can inject the desired amount of fluid lens-forming material into the molding cavity 16 in a continuous or discontinuous manner.

Since the casting opening 20 is located at the upper portion 11A of the molding cavity 16, gravity helps the flow of the fluid lens-forming material into the molding cavity 16. Therefore, it is not necessary to provide pumping means to fill the molding cavity. Moreover, because of gravity, the lens-forming material naturally fills the molding cavity 16 from the bottom up while the air bubbles B travel to the venting opening 18 without passing through the center region of the molding cavity 16. Consequently, the likelihood of having optical defects in the most optically active region of the formed lens is greatly reduced and better lenses can be made by practicing the present invention.

Once a proper amount of the fluid lens-forming material is introduced into the molding cavity 16, the filling needle is withdrawn from the cavity 16 and the closure member 14. The fluid lens-forming material is then cured and hardened. As one skilled in the art will appreciate, curing can be accomplished in a number of ways. For example, the curing method of the present invention involves exposing the fluid lens-forming material to an ultraviolet ("UV") light for a desired time. Alternatively, after exposing the fluid lens-forming material to UV light, the fluid lens-forming material is then heated for a predetermined time, such as in an infra-red ("IR") oven. The second heating step solidifies the fluid lens-forming material to form the hardened lens if the material is not sufficiently cured in the UV step.

Fig. 6 shows another or third embodiment of the present invention, wherein the closure member 14 has two casting openings 20A, 20B. The casting opening 20A is located at an angle  $\alpha_1$  apart from the venting opening 18 while the casting opening 20B is located at an angle  $\alpha_2$  apart from the venting opening 18. Angles  $\alpha_1$  and  $\alpha_2$  can be

different acute angles. However, they may have same value. In other words, the casting openings 20A, 20B may be symmetric about the venting opening 18, which is positioned at or adjacent to the highest or upper most point 17 on the molding cavity 16. Casting openings 20A, 20B allow two filling needles to introduce the fluid lens-  
5 forming material into the molding cavity 16 simultaneously and thus shorten the filling process significantly. Furthermore, the closure member 14 may have more than two casting openings. Again, each of the multiple casting openings can be located at a same or different angle apart from the venting opening than the rest of the casting openings. The casting openings may be symmetrically distributed about the venting  
10 opening. Or they may be asymmetrically distributed about the venting opening. It is not necessary to use every casting opening available to fill the mold. Nevertheless, incorporating a mold with multiple casting openings of the present invention with automation technology available in the art may greatly reduce the production time of molding an optical lens.

15

As discussed above and shown in Fig. 3, the closure member 14 can take a form of a sleeve that is formed from a strip. Figs. 8, 9 and 11 show several embodiments of the strip that can be utilized to practice the present invention.

20 Referring to Fig. 8, where a strip 70 of elastomeric material that can be used to form sleeve 14 is shown. The strip 70 has two opposing ends 72, 74, two opposing surfaces 26, 32 and a thickness H between the surfaces 26 and 32. Surfaces 26, 32 are substantially flat. The range of thickness H is 1 millimeter to 8 millimeter. In one embodiment, the range of thickness H can be 2 millimeter to 6 millimeter.

25 Alternatively, the range of thickness H can be 3 millimeter to 4 millimeter.

Fig. 9 shows an alternative form of a strip of elastomeric material that can be used to form sleeve 14. In Fig. 9, strip 80 has two opposing ends 72, 74, two opposing  
30 outer and inner surfaces 26, 32 and a thickness H between the outer and inner surfaces 26, 32. Outer and inner surfaces 26, 32 are substantially flat. Additionally, inner surface 32 may have a recess 82, extending from end 72 to end 74, as shown in Fig. 9. In this embodiment, the recess 82 is a continuous channel across the inner surface 32.

The recess 82 can be located substantially around the middle section of the inner surface 32 so that the recess 82 can be conveniently used as a venting channel and/or a passage for providing fluid communication between the cavity 16 and a fluid reservoir (not shown) once a sleeve 120 is formed from the strip 80, as shown in Fig. 10. In the embodiment shown in Fig. 10, the sleeve 120 has a venting opening 62 open to the ambient air that is formed by the portion of the recess channel 82 at the end 72 and the portion of the recess channel 82 at the end 74 when the ends 72 and 74 of the strip 80 are fastened together as shown in Fig. 10 to form sleeve 120. A casting opening (not shown) may be formed by a filling needle directly piercing through the sleeve 120 at a position located along the recess channel 82 and apart from the venting opening 62. As formed, the recess channel 82 can act as a casting port that is separated from the ambient air by the outer surface of the closure member and is in fluid communication with the molding cavity. Once a fluid lens-forming material is introduced into the molding cavity through a casting port or a filing needle in communication with the recess channel 82, the lens-forming material naturally fills the molding cavity from the bottom up while any air bubbles may travel to the venting opening 62 partially through part of the recess channel 82 without passing through the center region of the molding cavity.

The recess 82 may be located elsewhere per a user's choice as long as the recess 82 can be in fluid communication with the lens-forming fluid filled in the cavity 16. Moreover, the recess 82 may be square, rectangular, circular, oval, semi-oval, semi-circular, or other proper geometrical shapes cross-sectionally. For the embodiment of the present invention shown in Figs. 9 and 10, the recess 82 is semi-circular cross-sectionally.

Fig. 11 shows yet another alternative form of a strip of elastomeric material that can be used to form closure member 14. In Fig. 11, strip 1190 has two opposing ends 1192, 1194, two opposing inner and outer surfaces 1196, 1198 and a thickness H between the surfaces 1196 and 1198. Inner and outer surfaces 1196, 1198 are substantially flat. Additionally, inner surface 1192 may have a recess 1199, extending discontinuously from end 1192 to end 1194, as shown in Fig. 11. In this embodiment,

the recess 1199 is a discontinuous channel across at least part of the interior surface 1196. The recess 1199 can be located substantially around the middle section of the inner surface 1196 so that the recess 1199 can be conveniently used as a venting channel and/or a passage for providing fluid communication between the cavity 16 and a fluid reservoir (not shown) once a sleeve 1200 is formed from the strip 1190, as shown in Fig. 12.

In the embodiment shown in Fig. 12, the sleeve 1200 has a venting opening 1222 open to the ambient air that is formed by the portion of the recess channel 1199 at the end 1192 and the portion of the recess channel 1199 at the end 1194 when the ends 1192 and 1194 of the strip 1190 are fastened together as shown in Fig. 12 to form sleeve 1200. A casting opening 1220 may be formed by a filling needle directly piercing through the sleeve 1200 at a position located along the recess channel 1199 and apart from the venting opening 1222. Again, as formed, the recess channel 1199 can act as a casting port that is separated from the ambient air by the outer surface 1198 of the closure member and is in fluid communication with the molding cavity.

Alternatively, closure member 14 can take a form of a gasket. Fig. 13 shows one exemplary embodiment of a gasket that can be utilized to practice the present invention. In Fig. 13, gasket 1300 has a venting port 1322 and a casting port 1320. The venting port 1322 has a venting opening 1328 in fluid communication with the molding cavity and the ambient air. The casting port 1320 is formed in the body portion of the gasket 1300 between its outer surface 1326 and inner surface 1332. The casting port 1320 is in fluid communication with the molding cavity 16. The casting port 1320 is adapted to receive a portion of a needle therein so that the needle is in fluid communication with the cavity 16. Once a fluid lens-forming material is introduced into the molding cavity through the casting port 1320, the lens-forming material naturally fills the molding cavity from the bottom up while any air bubbles may travel to the venting opening 1322 and vent to the ambient air. Optionally, the venting port 1322 and the casting port 1320 can be connected by recess channel (not shown) similar to, for example, the recess channel 1199 as shown in Fig. 11. Additionally, casting port 1320 can have a casting support portion 1325 formed on the outer surface of the body



portion of gasket 1300. The casting support portion 1325 may be adapted to support or position a filling device such as a filling needle (not shown) for better filling.

Another aspect of the gasket such as gasket 1300 of the present invention is the  
5 gasket material. In one embodiment, a desirable characteristic is that the gasket material is chemically compatible with the lens-forming fluid to avoid inhibiting polymerization of the fluid. The gasket material should not include free-radical inhibitors, such as "UV" stabilizers and antioxidants. A UV stabilizer can leach into the monomer because the monomer acts almost like a solvent to draw such an additive  
10 out of the gasket material and to mix locally into the monomer, causing the edges of the lens remain slightly wet after curing. The wetness can be a problem because it potentially results in the monomer adhering to the gasket 1300 and molds contained therein, which requires cleaning before reuse and increases operating expenses. Accordingly, a desired gasket is a polymeric elastomer compatible with optical  
15 monomers which will not inhibit lens monomer during the curing process. Still another aspect of the gasket material is that it be relatively soft, for example having a durometer between 40 and 70. Another concern is whether the gasket material has long-term stabilities.

20 In several embodiments, a suitable gasket material is thermoplastic rubber that contains KRATON<sup>®</sup>G, a styrene-ethylene-propylene (butylene) block copolymer, sold by Shell Oil Company<sup>®</sup> of Houston, Texas. Such rubber includes those sold under the trade names DYNAFLEX<sup>®</sup>G2703, 2711, and 2712 by GLS Corporation of Cary, Illinois. These rubbers have a Shore A hardness ranging from about 43 to 62, a specific  
25 gravity of about 0.9g/cc, a tensile modulus at 300% elongation ranging from about 355 to 470, tensile strength at break of about 680 to 1000 psi, and a tear strength of about 113 to 127. Another contemplated gasket material includes a PVC formulation. The gasket material of the present invention, however, is not limited to a single material. In fact, the desired gasket material can vary depending on the specific monomer  
30 compound used to form the lens. That is, a certain gasket material may be utilized with a particular lens-forming fluid and different type of gasket material with another lens

material. Other contemplated materials include elastomeric PVC, silicon, ethylene vinyl acetate, or a mixture thereof.

5 The fluid lens-forming material can be a monomer. One monomer that can be used to practice the present invention is manufactured by P.P.G. located at Pittsburgh, Pennsylvania, and sold under the trademark CR 424. As one skilled in the art will appreciate, other lens-forming materials known in the art can be used with the present invention.

10 In practicing the present invention, as discussed above, the closure member 14 may be a gasket or a sleeve made from elastomeric material so that a filling needle may pierce through the sleeve to establish a fluid communication channel with the molding cavity. In several embodiments of the present invention, a suitable sleeve material is thermoplastic rubber that contains KRATON<sup>®</sup>G, a styrene-ethylene-propylene  
15 (butylene) block copolymer, sold by Shell Oil Company of Houston, Texas. Such rubber includes those sold under the trademarks DYNAFLEX<sup>®</sup>G2703, 2711, and 2712 by GLS Corporation of Cary, Illinois. These rubbers have a Shore A hardness ranging from about 43 to 62, a specific gravity of about 0.9g/cc, a tensile modulus at 300% elongation ranging from about 355 to 470, tensile strength at break of about 680 to  
20 1000 psi, and a tear strength of about 113 to 127. These rubbers have smooth surfaces and have a thickness in a range of 1 mm - 8 mm. The sleeve material of the present invention, however, is not limited to a single material. In fact, the desired sleeve material can vary depending on the specific monomer compound used to form the lens. That is, a certain sleeve material may be preferred with a particular lens-forming fluid  
25 and different type of sleeve material with another lens-forming material. Among many available materials, it is found that the present invention can be satisfactorily practiced with polyurethane, polyvinyl chloride, organosilicon elastomer as well as KRATON<sup>®</sup>G.

Although the present invention has been described with reference to specific  
30 details of certain embodiments thereof, it is not intended that such details should be regarded as limitations upon the scope of the invention except as and to the extent that

they are included in the accompanying claims. Many modifications and variations are possible in light of the above disclosure.

For example, the invention has been described with reference to use a venting  
5 opening to vent out air from the molding cavity. An air pump may be used to cooperate  
with the venting opening to outlet air from the molding cavity, which, of course, is  
made possible by the separation of the venting opening and the casting opening  
provided by the present invention. Moreover, just like plurality of casting openings  
may be utilized to facilitate placing a lens-forming fluid into a molding cavity, a  
10 plurality of venting openings may be used to outlet air from the molding cavity. For  
example, a plurality of venting openings can be arranged at the top of the upper portion  
of the mold, but spaced apart from each other.

11  
12  
13  
14  
15  
16  
17  
18  
19  
20  
21  
22  
23  
24  
25  
26  
27  
28  
29  
30  
31  
32  
33  
34  
35  
36  
37  
38  
39  
40  
41  
42  
43  
44  
45  
46  
47  
48  
49  
50  
51  
52  
53  
54  
55  
56  
57  
58  
59  
60  
61  
62  
63  
64  
65  
66  
67  
68  
69  
70  
71  
72  
73  
74  
75  
76  
77  
78  
79  
80  
81  
82  
83  
84  
85  
86  
87  
88  
89  
90  
91  
92  
93  
94  
95  
96  
97  
98  
99  
100  
101  
102  
103  
104  
105  
106  
107  
108  
109  
110  
111  
112  
113  
114  
115  
116  
117  
118  
119  
120  
121  
122  
123  
124  
125  
126  
127  
128  
129  
130  
131  
132  
133  
134  
135  
136  
137  
138  
139  
140  
141  
142  
143  
144  
145  
146  
147  
148  
149  
150  
151  
152  
153  
154  
155  
156  
157  
158  
159  
160  
161  
162  
163  
164  
165  
166  
167  
168  
169  
170  
171  
172  
173  
174  
175  
176  
177  
178  
179  
180  
181  
182  
183  
184  
185  
186  
187  
188  
189  
190  
191  
192  
193  
194  
195  
196  
197  
198  
199  
200  
201  
202  
203  
204  
205  
206  
207  
208  
209  
210  
211  
212  
213  
214  
215  
216  
217  
218  
219  
220  
221  
222  
223  
224  
225  
226  
227  
228  
229  
230  
231  
232  
233  
234  
235  
236  
237  
238  
239  
240  
241  
242  
243  
244  
245  
246  
247  
248  
249  
250  
251  
252  
253  
254  
255  
256  
257  
258  
259  
260  
261  
262  
263  
264  
265  
266  
267  
268  
269  
270  
271  
272  
273  
274  
275  
276  
277  
278  
279  
280  
281  
282  
283  
284  
285  
286  
287  
288  
289  
290  
291  
292  
293  
294  
295  
296  
297  
298  
299  
300  
301  
302  
303  
304  
305  
306  
307  
308  
309  
310  
311  
312  
313  
314  
315  
316  
317  
318  
319  
320  
321  
322  
323  
324  
325  
326  
327  
328  
329  
330  
331  
332  
333  
334  
335  
336  
337  
338  
339  
340  
341  
342  
343  
344  
345  
346  
347  
348  
349  
350  
351  
352  
353  
354  
355  
356  
357  
358  
359  
360  
361  
362  
363  
364  
365  
366  
367  
368  
369  
370  
371  
372  
373  
374  
375  
376  
377  
378  
379  
380  
381  
382  
383  
384  
385  
386  
387  
388  
389  
390  
391  
392  
393  
394  
395  
396  
397  
398  
399  
400  
401  
402  
403  
404  
405  
406  
407  
408  
409  
410  
411  
412  
413  
414  
415  
416  
417  
418  
419  
420  
421  
422  
423  
424  
425  
426  
427  
428  
429  
430  
431  
432  
433  
434  
435  
436  
437  
438  
439  
440  
441  
442  
443  
444  
445  
446  
447  
448  
449  
450  
451  
452  
453  
454  
455  
456  
457  
458  
459  
460  
461  
462  
463  
464  
465  
466  
467  
468  
469  
470  
471  
472  
473  
474  
475  
476  
477  
478  
479  
480  
481  
482  
483  
484  
485  
486  
487  
488  
489  
490  
491  
492  
493  
494  
495  
496  
497  
498  
499  
500  
501  
502  
503  
504  
505  
506  
507  
508  
509  
510  
511  
512  
513  
514  
515  
516  
517  
518  
519  
520  
521  
522  
523  
524  
525  
526  
527  
528  
529  
530  
531  
532  
533  
534  
535  
536  
537  
538  
539  
540  
541  
542  
543  
544  
545  
546  
547  
548  
549  
550  
551  
552  
553  
554  
555  
556  
557  
558  
559  
560  
561  
562  
563  
564  
565  
566  
567  
568  
569  
570  
571  
572  
573  
574  
575  
576  
577  
578  
579  
580  
581  
582  
583  
584  
585  
586  
587  
588  
589  
590  
591  
592  
593  
594  
595  
596  
597  
598  
599  
600  
601  
602  
603  
604  
605  
606  
607  
608  
609  
610  
611  
612  
613  
614  
615  
616  
617  
618  
619  
620  
621  
622  
623  
624  
625  
626  
627  
628  
629  
630  
631  
632  
633  
634  
635  
636  
637  
638  
639  
640  
641  
642  
643  
644  
645  
646  
647  
648  
649  
650  
651  
652  
653  
654  
655  
656  
657  
658  
659  
660  
661  
662  
663  
664  
665  
666  
667  
668  
669  
670  
671  
672  
673  
674  
675  
676  
677  
678  
679  
680  
681  
682  
683  
684  
685  
686  
687  
688  
689  
690  
691  
692  
693  
694  
695  
696  
697  
698  
699  
700  
701  
702  
703  
704  
705  
706  
707  
708  
709  
710  
711  
712  
713  
714  
715  
716  
717  
718  
719  
720  
721  
722  
723  
724  
725  
726  
727  
728  
729  
730  
731  
732  
733  
734  
735  
736  
737  
738  
739  
740  
741  
742  
743  
744  
745  
746  
747  
748  
749  
750  
751  
752  
753  
754  
755  
756  
757  
758  
759  
760  
761  
762  
763  
764  
765  
766  
767  
768  
769  
770  
771  
772  
773  
774  
775  
776  
777  
778  
779  
780  
781  
782  
783  
784  
785  
786  
787  
788  
789  
790  
791  
792  
793  
794  
795  
796  
797  
798  
799  
800  
801  
802  
803  
804  
805  
806  
807  
808  
809  
810  
811  
812  
813  
814  
815  
816  
817  
818  
819  
820  
821  
822  
823  
824  
825  
826  
827  
828  
829  
830  
831  
832  
833  
834  
835  
836  
837  
838  
839  
840  
841  
842  
843  
844  
845  
846  
847  
848  
849  
850  
851  
852  
853  
854  
855  
856  
857  
858  
859  
860  
861  
862  
863  
864  
865  
866  
867  
868  
869  
870  
871  
872  
873  
874  
875  
876  
877  
878  
879  
880  
881  
882  
883  
884  
885  
886  
887  
888  
889  
890  
891  
892  
893  
894  
895  
896  
897  
898  
899  
900  
901  
902  
903  
904  
905  
906  
907  
908  
909  
910  
911  
912  
913  
914  
915  
916  
917  
918  
919  
920  
921  
922  
923  
924  
925  
926  
927  
928  
929  
930  
931  
932  
933  
934  
935  
936  
937  
938  
939  
940  
941  
942  
943  
944  
945  
946  
947  
948  
949  
950  
951  
952  
953  
954  
955  
956  
957  
958  
959  
960  
961  
962  
963  
964  
965  
966  
967  
968  
969  
970  
971  
972  
973  
974  
975  
976  
977  
978  
979  
980  
981  
982  
983  
984  
985  
986  
987  
988  
989  
990  
991  
992  
993  
994  
995  
996  
997  
998  
999  
1000  
1001  
1002  
1003  
1004  
1005  
1006  
1007  
1008  
1009  
1010  
1011  
1012  
1013  
1014  
1015  
1016  
1017  
1018  
1019  
1020  
1021  
1022  
1023  
1024  
1025  
1026  
1027  
1028  
1029  
1030  
1031  
1032  
1033  
1034  
1035  
1036  
1037  
1038  
1039  
1040  
1041  
1042  
1043  
1044  
1045  
1046  
1047  
1048  
1049  
1050  
1051  
1052  
1053  
1054  
1055  
1056  
1057  
1058  
1059  
1060  
1061  
1062  
1063  
1064  
1065  
1066  
1067  
1068  
1069  
1070  
1071  
1072  
1073  
1074  
1075  
1076  
1077  
1078  
1079  
1080  
1081  
1082  
1083  
1084  
1085  
1086  
1087  
1088  
1089  
1090  
1091  
1092  
1093  
1094  
1095  
1096  
1097  
1098  
1099  
1100  
1101  
1102  
1103  
1104  
1105  
1106  
1107  
1108  
1109  
1110  
1111  
1112  
1113  
1114  
1115  
1116  
1117  
1118  
1119  
1120  
1121  
1122  
1123  
1124  
1125  
1126  
1127  
1128  
1129  
1130  
1131  
1132  
1133  
1134  
1135  
1136  
1137  
1138  
1139  
1140  
1141  
1142  
1143  
1144  
1145  
1146  
1147  
1148  
1149  
1150  
1151  
1152  
1153  
1154  
1155  
1156  
1157  
1158  
1159  
1160  
1161  
1162  
1163  
1164  
1165  
1166  
1167  
1168  
1169  
1170  
1171  
1172  
1173  
1174  
1175  
1176  
1177  
1178  
1179  
1180  
1181  
1182  
1183  
1184  
1185  
1186  
1187  
1188  
1189  
1190  
1191  
1192  
1193  
1194  
1195  
1196  
1197  
1198  
1199  
1200  
1201  
1202  
1203  
1204  
1205  
1206  
1207  
1208  
1209  
1210  
1211  
1212  
1213  
1214  
1215  
1216  
1217  
1218  
1219  
1220  
1221  
1222  
1223  
1224  
1225  
1226  
1227  
1228  
1229  
1230  
1231  
1232  
1233  
1234  
1235  
1236  
1237  
1238  
1239  
1240  
1241  
1242  
1243  
1244  
1245  
1246  
1247  
1248  
1249  
1250  
1251  
1252  
1253  
1254  
1255  
1256  
1257  
1258  
1259  
1260  
1261  
1262  
1263  
1264  
1265  
1266  
1267  
1268  
1269  
1270  
1271  
1272  
1273  
1274  
1275  
1276  
1277  
1278  
1279  
1280  
1281  
1282  
1283  
1284  
1285  
1286  
1287  
1288  
1289  
1290  
1291  
1292  
1293  
1294  
1295  
1296  
1297  
1298  
1299  
1300  
1301  
1302  
1303  
1304  
1305  
1306  
1307  
1308  
1309  
1310  
1311  
1312  
1313  
1314  
1315  
1316  
1317  
1318  
1319  
1320  
1321  
1322  
1323  
1324  
1325  
1326  
1327  
1328  
1329  
1330  
1331  
1332  
1333  
1334  
1335  
1336  
1337  
1338  
1339  
1340  
1341  
1342  
1343  
1344  
1345  
1346  
1347  
1348  
1349  
1350  
1351  
1352  
1353  
1354  
1355  
1356  
1357  
1358  
1359  
1360  
1361  
1362  
1363  
1364  
1365  
1366  
1367  
1368  
1369  
1370  
1371  
1372  
1373  
1374  
1375  
1376  
1377  
1378  
1379  
1380  
1381  
1382  
1383  
1384  
1385  
1386  
1387  
1388  
1389  
1390  
1391  
1392  
1393  
1394  
1395  
1396  
1397  
1398  
1399  
1400  
1401  
1402  
1403  
1404  
1405  
1406  
1407  
1408  
1409  
1410  
1411  
1412  
1413  
1414  
1415  
1416  
1417  
1418  
1419  
1420  
1421  
1422  
1423  
1424  
1425  
1426  
1427  
1428  
1429  
1430  
1431  
1432  
1433  
1434  
1435  
1436  
1437  
1438  
1439  
1440  
1441  
1442  
1443  
1444  
1445  
1446  
1447  
1448  
1449  
1450  
1451  
1452  
1453  
1454  
1455  
1456  
1457  
1458  
1459  
1460  
1461  
1462  
1463  
1464  
1465  
1466  
1467  
1468  
1469  
1470  
1471  
1472  
1473  
1474  
1475  
1476  
1477  
1478  
1479  
1480  
1481  
1482  
1483  
1484  
1485  
1486  
1487  
1488  
1489  
1490  
1491  
1492  
1493  
1494  
1495  
1496  
1497  
1498  
1499  
1500  
1501  
1502  
1503  
1504  
1505  
1506  
1507  
1508  
1509  
1510  
1511  
1512  
1513  
1514  
1515  
1516  
1517  
1518  
1519  
1520  
1521  
1522  
1523  
1524  
1525  
1526  
1527  
1528  
1529  
1530  
1531  
1532  
1533  
1534  
1535  
1536  
1537  
1538  
1539  
1540  
1541  
1542  
1543  
1544  
1545  
1546  
1547  
1548  
1549  
1550  
1551  
1552  
1553  
1554  
1555  
1556  
1557  
1558  
1559  
1560  
1561  
1562  
1563  
1564  
1565  
1566  
1567  
1568  
1569  
1570  
1571  
1572  
1573  
1574  
1575  
1576  
1577  
1578  
1579  
1580  
1581  
1582  
1583  
1584  
1585  
1586  
1587  
1588  
1589  
1590  
1591  
1592  
1593  
1594  
1595  
1596  
1597  
1598  
1599  
1600  
1601  
1602  
1603  
1604  
1605  
1606  
1607  
1608  
1609  
1610  
1611  
1612  
1613  
1614  
1615  
1616  
1617  
1618  
1619  
1620  
1621  
1622  
1623  
1624  
1625  
1626  
1627  
1628  
1629  
1630  
1631  
1632  
1633  
1634  
1635  
1636  
1637  
1638  
1639  
1640  
1641  
1642  
1643  
1644  
1645  
1646  
1647  
1648  
1649  
1650  
1651  
1652  
1653  
1654  
1655  
1656  
1657  
1658  
1659  
1660  
1661  
1662  
1663  
1664  
1665  
1666  
1667  
1668  
1669  
1670  
1671  
1672  
1673  
1674  
1675  
1676  
1677  
1678  
1679  
1680  
1681  
1682  
1683  
1684  
1685  
1686  
1687  
1688  
1689  
1690  
1691  
1692  
1693  
1694  
1695  
1696  
1697  
1698  
1699  
1700  
1701  
1702  
1703  
1704  
1705  
1706  
1707  
1708  
1709  
1710  
1711  
1712  
1713  
1714  
1715  
1716  
1717  
1718  
1719  
1720  
1721  
1722  
1723  
1724  
1725  
1726  
1727  
1728  
1729  
1730  
1731  
1732  
1733  
1734  
1735  
1736  
1737  
1738  
1739  
1740  
1741  
1742  
1743  
1744  
1745  
1746  
1747  
1748  
1749  
1750  
1751  
1752  
1753  
1754  
1755  
1756  
1757  
1758  
1759  
1760  
1761  
1762  
1763  
1764  
1765  
1766  
1767  
1768  
1769  
1770  
1771  
1772  
1773  
1774  
1775  
1776  
1777  
1778  
1779  
1780  
1781  
1782  
1783  
1784  
1785  
1786  
1787  
1788  
1789  
1790  
1791  
1792  
1793  
1794  
1795  
1796  
1797  
1798  
1799  
1800  
1801  
1802  
1803  
1804  
1805  
1806  
1807  
1808  
1809  
1810  
1811  
1812  
1813  
1814  
1815  
1816  
1817  
1818  
1819  
1820  
1821  
1822  
1823  
1824  
1825  
1826  
1827  
1828  
1829  
1830  
1831  
1832  
1833  
1834  
1835  
1836  
1837  
1838  
1839  
1840  
1841  
1842  
1843  
1844  
1845  
1846  
1847  
1848  
1849  
1850  
1851  
1852  
1853  
1854  
1855  
1856  
1857  
1858  
1859  
1860  
1861  
1862  
1863  
1864  
1865  
1866  
1867  
1868  
1869  
1870  
1871  
1872  
1873  
1874  
1875  
1876  
1877  
1878  
1879  
1880  
1881  
1882  
1883  
1884  
1885  
1886  
1887  
1888  
1889  
1890  
1891  
1892  
1893  
1894  
1895  
1896  
1897  
1898  
1899  
1900  
1901  
1902  
1903  
1904  
1905  
1906  
1907  
1908  
1909  
1910  
1911  
1912  
1913  
1914  
1915  
1916  
1917  
1918  
1919  
1920  
1921  
1922  
1923  
1924  
1925  
1926  
1927  
1928  
1929  
1930  
1931  
1932  
1933  
1934  
1935  
1936  
1937  
1938  
1939  
1940  
1941  
1942  
1943  
1944  
1945  
1946  
1947  
1948  
1949  
1950  
1951  
1952  
1953  
1954  
1955  
1956  
1957  
1958  
1959  
1960  
1961  
1962  
1963  
1964  
1965  
1966  
1967  
1968  
1969  
1970  
1971  
1972  
1973  
1974  
1975  
1976  
1977  
1978  
1979  
1980  
1981  
1982  
1983  
1984  
1985  
1986  
1987  
1988  
1989  
1990  
1991  
1992  
1993  
1994  
1995  
1996  
1997  
1998  
1999  
2000  
2001  
2002  
2003  
2004  
2005  
2006  
2007  
2008  
2009  
2010  
2011  
2012  
2013  
2014  
2015  
2016  
2017  
2018  
2019  
2020  
2021  
2022  
2023  
2024  
2025  
2026  
2027  
2028  
2029  
2030  
2031  
2032  
2033  
2034  
2035  
2036  
2037  
2038  
2039  
2040  
2041  
2042  
2043  
2044  
2045  
2046  
2047  
2048  
2049  
2050  
2051  
2052  
2053  
2054  
2055  
2056  
2057  
2058  
2059  
2060  
2061  
2062  
2063  
2064  
2065  
2066  
2067  
2068  
2069  
2070  
2071  
2072  
2073  
2074  
2075  
2076  
2077  
2078  
2079  
2080  
2081  
2082  
2083  
2084  
2085  
2086  
2087  
2088  
2089  
2090  
2091  
2092  
2093  
2094  
2095  
2096  
2097  
2098  
2099  
2100  
2101  
2102  
2103  
2104  
2105  
2106  
2107  
2108  
2109  
2110  
2111  
2112  
2113  
2114  
2115  
2116  
2117  
2118  
2119  
2120  
2121  
2122  
2123  
2124  
2125  
2126  
2127  
2128  
2129  
2130  
2131  
2132  
2133  
2134  
2135  
2136  
2137  
2138  
2139  
2140  
2141  
2142  
2143  
2144  
2145  
2146  
2147  
2148  
2149  
2150  
2151  
2152  
2153  
2154  
2155  
2156  
2157  
2158  
2159  
2160  
2161  
2162  
2163  
2164  
2165  
2166  
2167  
2168  
2169  
2170  
2171  
2172  
2173  
2174  
2175  
2176  
2177  
2178  
2179  
2180  
2181  
2182  
2183  
2184  
2185  
2186  
2187  
2188  
2189  
2190  
2191  
2192  
2193